Perfect solution for the replacement of halogen lamps in spotlights. Compared to any halogen lamp, Canyon LED does not emit a huge amount of heat. Suitable for general and accent lighting with 60 and 38 degrees beam angle. The lamps are presented with different types of bases GU10 and GU5.3. CANYON LED lamps lighten objects without distorting their true colors, so original colors will retain everywhere.





CANYON ICE COB module for all Canyon LED lamps. In comparison to SMD technology widely used in usual LED lamps, Canyon LED heats less providing stable light output and longer lifetime.

Compared to drivers, which are used in many LED lamps, our power adaptors have perfect design, heat less and provide efficient power delivery to the lamp.

Canyon products fully comply with all requirements of the EC directives and harmonized standards of the European Union, which has been proved by CE certificate. Our factories are certified by TUV Rheinland, Germany according to the highest European standards SA 8000, ISO14001, ISO 9001 and ISO 17025.


Honest features without valueless advertising promises

All declared specifications strictly correspond to the actual characteristics of the product. We are so confident in our product that we give warranty with easy-to-change procedure.

Environment-friendly product
High European environmental standards are proved by RoHS certificate. Lamps do not contain harmful heavy

> SPOT LAMPS Neutral, 4000K





Color Rendering > 80 Dimmina No. on demand Diameter, mm





50

Diameter, mm



watt w w	₩ Im
Article	MRGU53/8W230VN38
EAN	8717371864972
Cap (base)	GU5.3
Voltage	220 - 240
Correlated Color Temperature, K	4000
Color Rendering Index, Ra	> 80
Lifetime	50 000
Dimming	No, on demand
Overall length, mm	54,0
Diameter, mm	50
Gross weight, g	76

MR16 7.5 255 38° 594 A+



Watt Watt	00 394 F	۲,
Article	MRGU53/8W230\	/N6
EAN	871737186498	9
Cap (base)	GU5.3	
Voltage	220 - 240	
Correlated Color Temperature, K	4000	
Color Rendering Index, Ra	> 80	
Lifetime	50 000	
Dimming	No, on demand	
Overall length, mm	54,0	
Diameter, mm	50	
Gross weight, g	76	

MP16 7 5 = 55 60° 504 A+

